

ARTRAY

ARTCAM 系列

传感器类型	接口	像素数	型号		摄影尺寸	像素大小	快门类型	帧率 (fps)	直接对应	近红外类型	ROI 功能	监视器输出	I/O 对应	LINUX 对应	HALCON 对应	LabVIEW 对应
			彩色	黑白												
CCD	USB2.0	500MI	ARTCAM-500P	-	2/3"	3.4×3.4	面阵	3.75	●	-	-	-	-	-	●	●
		200MI	ARTCAM-274KY	ARTCAM-274KY-BW	1/1.8"	4.4×4.4	面阵	10	●	-	-	-	-	-	●	●
		150MI	ARTCAM-150P III	ARTCAM-150P III-BW	1/2"	4.65×4.65	面阵	12	●	-	-	●	-	-	●	●
	Serial ATA	500MI	ARTCAM-425KY-SATA	ARTCAM-425KY-SATA-BW	2/3"	3.45×3.45	面阵	8	-	-	-	-	-	-	-	-
		200MI	ARTCAM-274KY-SATA	-	1/1.8"	4.4×4.4	面阵	15	-	-	-	-	-	-	-	-
		150MI	ARTCAM-287KY-SATA	ARTCAM-287KY-SATA-BW	1/2"	4.65×4.65	面阵	18	-	-	-	-	-	-	-	-
CMOS	USB2.0	500MI	ARTCAM-500MI	-	1/2.5"	2.2×2.2	线阵	3.75	-	-	●	-	●	-	-	
		300MI	ARTCAM-300MI	-	1/2"	3.2×3.2	线阵	8	●	-	●	●	●	-	●	●
		130MI	ARTCAM-130MI	ARTCAM-130MI-BW	1/2"	5.2×5.2	线阵	15	●	●	●	●	●	-	●	●
		36MI	ARTCAM-036MI	ARTCAM-036MI-BW	1/3"	6.0×6.0	面阵	60	●	●	●	-	●	●	●	●
		36MI	ARTCAM-036ME	ARTCAM-036ME-BW	1/3"	6.0×6.0	面阵	60	●	-	●	-	-	●	●	●
	Serial ATA	500MI	ARTCAM-500ME-SATA	-	1/2.5"	2.2×2.2	线阵	10	-	-	●	-	-	-	-	-
		300MI	ARTCAM-300ME-SATA	-	1/2"	3.2×3.2	线阵	18	-	-	●	-	-	-	-	-
		130MI	ARTCAM-200ME-SATA	-	1"	12×12	线阵	4806b①	-	●	●	-	-	-	-	-
		130MI	ARTCAM-130ME-SATA	ARTCAM-130ME-SATA-BW	1/2"	5.2×5.2	线阵	32	-	●	●	-	-	-	-	-
		36MI	ARTCAM-036ME-SATA	ARTCAM-036ME-SATA-BW	1/3"	6.0×6.0	面阵	74	-	●	●	-	-	-	-	-

红外线USB2.0相机 ARTCAM-320 THERMO	
检测器	非冷却micron polo meter
有效像素	320(H)×240(V)
帧频	25FPS
图像pitch	23.5um
扫描方式	逐行扫描
检测波长	8 - 14um
镜头视角	50°(H)×37°(V)
输出	USB2.0(14bit数字输出)
尺寸	75W×75H×86D
电源	+12V 1A

Usb2.0变频 (NTSC-EIA-SECAM-USB2.0)			
型号	输入方式	链接台数	直接对应
ARTCNV II -PIN	RCA pin type	1	●
ARTCNV II -BNC	BNC pin type	1	●
ARTCNV II -12P	12 pin type	1	●
ARTOM II -PM-3CH	RCA pin type	2	●
ARTOM II -BNC-2CH	BNC pin type	2	●
ARTOM II -12P-2CH	12 pin type	2	●
ARTOM II -PM-3CH	RCA pin type	3	●
ARTOM II -BNC-3CH	BNC pin type	3	●
ARTOM II -12P-3CH	12 pin type	3	●
ARTCNV II -HAKO	RCA pin type	6	●

SATA变频相机 (LVDS相机-SATA)		
型号	输入方式	链接台数
ARTSAT-0506-LV	LVDS	1

USB2.0变频 (LVDS相机 USB2.0)		
型号	输入方式	链接台数
ARTJUST-0405A	LVDS	1